

10,4" TFT MONITOR FOR ATM NCR 5674



General :

This TFT built-in monitor has been developed as a universal solution for replacement of the 14" CRT monitor in a NCR 5674 ATM. The compatibility for this monitor is ensured by appropriate mounting plates and functional adjustments:

- Easy installation into existing ATMs
- No burn-in problems as with CRTs
- Warranty 24 months
- Mechanically and electronically 100% compatible (Plug & Play)

Technical Data	TFT-10,4 inch / NCR 5674
Display:	Standard
Display size	10,4"
Brightness	350 cd/m ₂
Resolution-Timings:	640x480 dots annualized to DOS / VGA / SVGA
Input Signal:	
Videonorm	VGA RGB analog
H. Frequency	31 - 35 kHz
V. Frequency	50 - 75 Hz
Sync. signal	H/V seperated, TTL level
Pixelclock	max. 30 MHz
Colours	6 bit per colours
Adjustments (OSD):	Brightness, Contrast, Horizontal position, Vertical Position, Default; Settings saved automatically
Power Management:	Background lighting is switched off by missing video signal.
Connections:	
Input signal :	15 pol. SUB-D high density
Power supply :	230 V AC
Power consumption:	approx. 30 W
Operation conditions:	Operating temperature 0° - 50°C
MTBF:	Background lighting 50.000 hours / 25°C
Weight:	ca. 5,5 Kg (12.1 lbs)
Manufactured acc. to:	EMV: EN55022, EN55024, EN61000; CE: EN60950 conform
Scope of delivery:	10,4" Chassis + assembly kit
Optional:	privacy filter
Versions:	009-0009632 009-0009633 009-0009868 009-0010904 009-0011972