

8,4” TFT Monitor for ATMs



General :

This built-in monitor is a special solution for change cathode ray tube monitors (CRT) and is both in standard type and in transreflective panel version available

The transreflective monitor is based on the newest state-of-the-art technology in the market. This solution offers a reflector that is behind the real LCD segment, which reflects the complete incoming light from the front side.

The reflecting brightness from inside depends on the brightness from outside.

-> Higher sunlight – better clearness of the display !

This display technology is an absolute alternative to the previous sunlight monitors, with the following additional assets:

- low power usage (because normal background lighting)
- no automatic control of the background lighting necessary
- longer life cycle, because less sensitive technic
- lower pricing, because of lower technical investments

At present for following models insertable:

- Wincor Nixdorf CSC 4xx
- Wincor ProCash 400

The monitor set is complete with fittings – the time work for change the CRT monitor locally is amounting to max. 20 minutes -> plug and play !

Technical Data**TFT-8,4 inch****Display:**

Display size

Brightness

Contrast

Standard

8,4"

400 cd/m₂

500:1

Transflective

8,4"

600 cd/m₂ (Basic)

similar as 1200 cd/m on sunshine

700:1

Input signal:

Videonorm

H. frekvence

V. frekvence

Sync. signal

Pixelclock

Colours

VGA RGB analog

31 - 35 kHz

50 – 75 Hz

H/V separated, TTL level

max. 30 MHz

6 bit per colour

VGA RGB analog

31 - 35 kHz

58 - 62 Hz

H/V separated, TTL level

max. 30 MHz

6 bit per colour

Resolution timings:

max. 800x600 pixel

max. 800x600 pixel

supports: DOS / VGA / SVGA / XGA

Adjustments (OSD):brightness, contrast, horizontal position, vertical position,
default; settings saved automatically**Connections:**

Signal input

-> 15 pol.SUB-D

-> DVI

Power

230 V/ AC - rubber connector

Power consumption

approx. 30 W / transflective: approx. 40 W

Power management

background lighting is switched off by missing video signal

Operating conditions:

Operating temperature: 0° - 50°C (32° - 122° F)

MTBD:

Background lighting approx. 50.000 hours / 25°C (77° F)

Weight:

approx. 3,5 Kg (7.7 lbs)

Manufactured according to:

EMC: EN55022, EN55024, EN61000; CE-conform: EN60950

Delivery volume:

8,4" chassis with monitor fittings

Optional:

Privacy filter (LCF)

Warranty:

24 month

Versions:

WNI ProCash 400 / CSC4xx

NCR 5670 / 5870 (S70)

NCR 5684 / 5884 (S84)

NCR 5885 (S85)

IBM 473x + 478x

Diebold 10xxix (10")

Diebold Hector 6810

Diebold BQ 1410